

POWER GENERATOR 2800 W

- 6 HP engine pull cable starter
- Powerful and air cooled 4 stroke petrol engine with 212 cm³ displacement
- Max. 2800 W output power, 2500 W rated output
- Two 230 V connections and one 12 V DC connector
- Sturdy and robust steel frame with wheel kit and hinged handles
- Integrated overload protection, voltmeter and low oil warning

OPTIONAL ACCESSORIES

OIL ULTRA
PERFORMANCE
LONGLIFE
SAE 5W-40
500 ml



Article number: 3906100701
Barcode: 4014915073512



SPECIFICATIONS - GENERATOR	
Dimensions L x W x H	660 x 600 x 500 mm
Voltage control	AVR-System
Rated output / max. output	2500 / 2800 W
Socket	2 x 230 V~
AC frequency	50 Hz
Overload protection	Yes
Low oil warning	Yes
Voltmeter	Yes

SPECIFICATIONS - ENGINE	
Model	Single-cylinder; 4 stroke petrol engine
Max. engine power	6 HP
Displacement	212 cc
Starter	Pull starter
Tank capacity	15 L
Fuel consumption 2/3 load	1,05 L/h
Fuel consumption at max. load	3,89 L/h

LOGISTICAL DATA	
Weight net / gross	44,7 / 47 kg
Packaging dimensions	685 x 490 x 495 mm
Article number	5906226903
Barcode	4046664194668
40 HQ Container	375 pcs



EXAMPLES OF USE

Camping



Garden shed



Event



Construction site



Large tank capacity
(15 litres)

Sturdy and
robust steel
frame

Easy to manoeuvre
thanks to transport
handles and large wheels

212 cc, 6 HP,
4-stroke petrol engine

PRODUCT DETAILS

2 x 230 V power outlet



Lasting



Robust



Powerful



Fuel-saving



Power pack



Transportable



AVR technology minimises
voltage fluctuations and
ensures consistent power
from the generator

our SG3200x
traditional manufacturers

